WELDING GLOVE

Ref. 2530

TECHNICAL SHEET

MEASUREMENTS

Size	10
Ref.	2530
Total length (mm)	350
Palm thickness (mm)	1.2
Cuff thickness	1.3
Entrance glove width (mm)	140
Palm width (mm)	135

GENERAL DESCRIPTION AND MATERIALS

- Welding glove
- **Full split cow leather**
- **Wing thumb**
- **Split cuff, 15 cm**

SPECIFICAL ADVANTAGES

- Comfort
- Suppleness

MAIN APPLICATION FIELDS

- **Welding jobs**
- Metallurgical industry

PACKAGING

- Packed **by 10**
- **120 pairs** in a box

STANDARDIZATION

This glove is in conformity with the model of individual safety equipment which correspond to

The CE Type-examination certificate 0075/108/162/04/10/0156

Delivered by **CTC (notified body n° 0075)**

EN 420:2003

and EN 388:2003



2122

- **Abrasion** = 2/4
- **Blade cut** = 1/5
- **Tear** = 2/4
- **Puncture** = 2/4

EN 407:2004

41XX4X

- Resistance to **flammability** = 4/4
- Resistance to **contact heat** = 1/4
- Resistance to **convective heat** = X
- Resistance to **radiant heat** = X
- Resistance to **small splashes of molden metal** = 4/4
- Resistance to **large splashes of molden metal** = X

SACLA – Z.I. de Rosarge – 01700 LES ECHETS – MIRIBEL – FRANCE

Tèl. : (33) 04 72 26 57 57 – Fax. : (33) 04 72 26 51 70 – Mail : contact@sacla-france.com