WELDING GLOVE

Ref. 2631

TECHNICAL SHEET

MEASUREMENTS

Size	10
Ref.	2631
Total length (mm)	350
Entrance glove width (mm)	150
Palm width (mm)	150

GENERAL DESCRIPTION AND MATERIALS

- Welding glove
- **Split cow leather**
- **Split cuff, 15 cm**
- **Interior : thick lining**
- Colour : red

SPECIFICAL ADVANTAGES

- Comfort
- Interior : thick lining

MAIN APPLICATION FIELDS

- **Welding jobs**
- Metallurgical industry
- Protects against contact heat (100 °C during 15s max.)

PACKAGING

- Packed **by 12**
- **60 pairs** in a box

STANDARDIZATION

This glove is in conformity with the model of individual safety equipment which correspond to

The CE Type-examination certificate 8239 issue 1

delivered by **SATRA (n° 0321)**

EN 420:2003+A1:2009
EN 388:2003

3133

- **Abrasion** = 3/4
- **Blade cut** = 1/5
- **Tear** = 3/4
- **Puncture** = 3/4

EN 407:2004

41314X

- Resistance to **flammability** = 4/4
- Resistance to **contact heat** = 1/4
- Resistance to **convective heat** = 3/4
- Resistance to **radiant heat** = 1/4
- Resistance to **small splashes of molden metal** = 4/4
- Resistance to **large splashes of molden metal** = X

SACLA INTERNATIONAL - Z.I. de Rosarge – 01700 LES ECHETS – MIRIBEL – France
Tél. : (33) 04 72 26 59 60 – Fax. : (33) 04 72 26 59 61 – Mail : export@sacla-international.com